



Product Service

CERTIFICATE

No. Z2 072092 0288 Rev. 04

Model(s):

Maximum System Voltage: 1000 V DC or 1500 V DC
 JAM72S01-xxx/PR, JAM72S04-xxx/PR, JAM72S06-xxx/PR,
 xxx=325 to 390 in step of 5;
 JAM60S01-xxx/PR, JAM60S04-xxx/PR, JAM60S06-xxx/PR,
 xxx=280 to 325 in step of 5;
 JAM72S01-xxx/SC, JAM72S04-xxx/SC, xxx =320 to 365 in step of 5;
 JAM60S01-xxx/SC, JAM60S04-xxx/SC, JAM60S06-xxx/SC,
 xxx=265 to 300 in step of 5;
 JAM72S03-xxx/PR, xxx=355 to 400 in step of 5;
 JAM60S03-xxx/PR, xxx = 295 to 335 in step of 5;
 JAM72S01-xxx/MR, xxx= 360 to 390 in step of 5;
 JAM60S01-xxx/MR, xxx= 300 to 330 in step of 5;
 JAM72S09-xxx/PR, xxx= 370 to 390 in step of 5;
 JAM60S09-xxx/PR, xxx= 310 to 325 in step of 5;
 JAM72S10-xxx/PR, xxx= 380 to 415 in step of 5;
 JAM60S10-xxx/PR, xxx= 315 to 345 in step of 5;
 JAM72S10-xxx/MR, xxx= 390 to 410 in step of 5;
 JAM60S10-xxx/MR, xxx= 320 to 340 in step of 5;

Maximum System Voltage: 1500 V DC
 JAM6-72-xxx/SI/1500V, xxx =285 to 325 in step of 5;
 JAM6-60-xxx/SI/1500V, xxx =235 to 280 in step of 5;
 JAM6(R)-72-xxx/1500V, xxx =295 to 340 in step of 5;
 JAM6(R)-60-xxx/1500V, JAM6-60-xxx/4BB/1500V, xxx =255 to 280 in step of 5;
 JAM6-72-xxx/4BB/1500V, xxx =310 to 335 in step of 5;
 JAM6(L)-72-xxx/PR/1500V, xxx =325 to 345 in step of 5;
 JAM6(L)-60-xxx/PR/1500V, xxx =270 to 295 in step of 5;
 JAM6(K)-72-xxx/PR/1500V, xxx= 335 to 360 in step of 5;
 JAM6(K)-60-xxx/PR/1500V, xxx= 280 to 300 in step of 5;
 JAM6(K)-72-xxx/4BB/1500V, xxx =320 to 340 in step of 5;
 JAM6(K)-60-xxx/4BB /1500V, xxx =265 to 285 in step of 5;

Maximum System Voltage: 1000 V DC
 JAM5(R)-72-xxx, JAM5(R)(BK)-72- xxx, xxx= 195 to 220 in step of 5;
 JAM5-72-xxx, JAM5(BK)-72-xxx, xxx= 155 to 195 in step of 5;
 JAM5(L)-72-xxx, JAM5(L)(BK)-72-xxx, xxx= 155 to 215 in step of 5;
 JAM5-72-xxx/SI, JAM5(BK)-72-xxx/SI, xxx= 180 to 210 in step of 5;
 JAM5(L)-72-xxx/SI, JAM5(L)(BK)-72-xxx/SI, xxx= 180 to 220 in step of 5;
 JAM5(L)-96-xxx, JAM5(L)(BK)-96-xxx, xxx= 210 to 260 in step of 5;
 JAM5(L)-96-xxx/SI, JAM5(L)(BK)-96-xxx/SI; xxx= 240 to 290 in step of 5;
 JAM6-72-xxx, JAM6(BK)-72-xxx, xxx= 255 to 305 in step of 5;
 JAM6-72-xxx/SI, JAM6(BK)-72-xxx/SI, JAM6(SE)-72-xxx/SI,
 xxx= 285 to 325 in step of 5;
 JAM6-60-xxx, JAM6(BK)-60-xxx, xxx= 200 to 250 in step of 5;
 JAM6-60-xxx/3BB, JAM6(BK)-60-xxx/3BB, xxx= 200 to 275 in step of 5;
 JAM6-60-xxx/SI, JAM6(BK)-60-xxx/SI, JAM6(SE)-60-xxx/SI,
 xxx= 235 to 280 in step of 5;
 JAM6-54-xxx, JAM6(BK)-54-xxx; xxx= 180 to 225 in step of 5;
 JAM6-54-xxx/3BB, JAM6(BK)-54-xxx/3BB; xxx= 180 to 250 in step of 5;
 JAM6-72-xxx/3BB, JAM6(BK)-72-xxx/3BB, xxx= 310 to 330 in step of 5;
 JAM6-54-xxx/SI, JAM6(BK)-54-xxx/SI, xxx= 225 to 240 in step of 5;
 JAM6(R)-54-xxx, JAM6(R)(BK)-54-xxx, xxx=230 to 250 in step of 5;
 JAM6(R)-48-xxx, JAM6(R)(BK)-48-xxx, xxx=205 to 225 in step of 5;
 JAM6-48-xxx/SI, JAM6(BK)-48-xxx/SI, xxx=200 to 220 in step of 5;
 JAM6(R)-72-xxx, JAM6(R)(BK)-72-xxx, xxx=295 to 340 in step of 5;
 JAM6(R)-60-xxx, JAM6(R)(BK)-60-xxx, JAM6(L)-60-xxx,
 JAM6(L)(BK)-60-xxx, JAM6-60-xxx/4BB, xxx=255 to 280 in step of 5;
 JAM6(L)-72-xxx, JAM6(L)(BK)-72-xxx, xxx=295 to 335 in step of 5;
 JAM6(TG)-60-xxx/SI, JAM6(BK)(TG)-60-xxx/SI, JAM6(BK)(SE)-60-xxx/SI,
 xxx=250 to 280 in step of 5;
 JAM6(FA)-60-xxx/SI, xxx=255 to 275 in step of 5;
 JAM6(FA)-48-xxx/SI, xxx=205 to 220 in step of 5;
 JAM6(R)(FA)-48-xxx, JAM6(K)-48-xxx/4BB, JAM6(K)(BK)-48-xxx/4BB,
 xxx= 210 to 225 in step of 5;

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT

CERTIFICATE

No. Z2 072092 0288 Rev. 04

Model(s):

JAM6-72-xxx/4BB, xxx=310 to 335 in step of 5;
 JAM6(R)-72-xxx/PR, JAM6(R)(BK)-72-xxx/PR, xxx=330 to 350 in step of 5;
 JAM6(R)-60-xxx/PR, JAM6(R)(BK)-60-xxx/PR, xxx=280 to 295 in step of 5;
 JAM6(R)-48-xxx/PR, JAM6(R)(BK)-48-xxx/PR, JAM6(K)-48-xxx/PR,
 JAM6(K)(BK)-48-xxx/PR, xxx=220 to 235 in step of 5;
 JAM6-72-xxx/PR, JAM6(BK)-72-xxx/PR, JAM6(L)-72-xxx/PR,
 JAM6(L)(BK)-72-xxx/PR, JAM6(L)(TG)-72-xxx/PR,
 JAM6(L)(BK)(TG)-72-xxx/PR, xxx=325 to 345 in step of 5;
 JAM6(L)-60-xxx/PR, JAM6(L)(BK)-60-xxx/PR, xxx=270 to 295 in step of 5;
 JAM6(L)-54-xxx/PR, JAM6(L)(BK)-54-xxx/PR, xxx=250 to 270 in step of 5;
 JAM6-48-xxx/PR, JAM6(BK)-48-xxx/PR, JAM6(L)-48-xxx/PR,
 JAM6(L)(BK)-48-xxx/PR, xxx=215 to 235 in step of 5;
 JAM6(R)(SE)-72-xxx, JAM6(R)(BK)(SE)-72-xxx, xxx=305 to 330 in step of 5;
 JAM6(R)(FA)-60-xxx, JAM6(R)(SE)-60-xxx, JAM6(R)(BK)(SE)-60-xxx,
 JAM6(R)(TG)-60-xxx, JAM6(R)(BK)(TG)-60-xxx, xxx=260 to 280 in step of 5;
 JAM6(L)(SE)-60-xxx/PR, JAM6(L)(TG)-60-xxx/PR, JAM6(L)(BK)(SE)-60-xxx/PR,
 JAM6-60-xxx/PR, JAM6(BK)-60-xxx/PR, xxx=275 to 295 in step of 5;
 JAM6(TG)-72-xxx/SI, JAM6(BK)(TG)-72-xxx/SI, JAM6(BK)(SE)-72-xxx/SI,
 xxx=300 to 325 in step of 5;
 JAM6(R)(TG)-72-xxx, JAM6(R)(BK)(TG)-72-xxx, xxx=305 to 340 in step of 5;
 JAM6(L)-72-xxx/4BB, JAM6(L)(BK)-72-xxx/4BB, xxx=320 to 335 in step of 5;
 JAM6(L)-60-xxx/4BB, JAM6(L)(SE)-60-xxx/4BB,
 JAM6(L)(TG)-60-xxx/4BB, JAM6(L)(BK)-60-xxx/4BB,
 JAM6(L)(BK)(SE)-60-xxx/4BB, JAM6(L)(BK)(TG)-60-xxx/4BB,
 xxx= 265 to 280 in step of 5;
 JAM6(K)-72-xxx/4BB, JAM6(K)(BK)-72-xxx/4BB, JAM6(K)(TG)-72-xxx/4BB,
 xxx= 320 to 340 in step of 5;
 JAM6(K)-54-xxx/4BB, xxx= 235 to 250 in step of 5;
 JAM6(K)-72-xxx/PR, JAM6(K)(BK)-72-xxx/PR, JAM72S02-xxx/PR,
 JAM6(K)(BK)(TG)-72-xxx/PR, JAM6(K)(TG)-72-xxx/PR,
 xxx=325 to 360 in step of 5;
 JAM6(K)-60-xxx/PR, JAM6(K)(BK)-60-xxx/PR, xxx= 275 to 305 in step of 5;
 JAM6(K)-54-xxx/PR, JAM6(K)(BK)-54-xxx/PR, xxx= 250 to 265 in step of 5;
 JAM6(K)-60-xxx/4BB, JAM6(K)(BK)-60-xxx/4BB, JAM6(K)(SE)-60-xxx/4BB,
 JAM6(K)(BK)(SE)-60-xxx/4BB, JAM6(K)(TG)-60-xxx/4BB,
 JAM6(K)(BK)(TG)-60-xxx/4BB, JAM6(K)(FA)-60-xxx/4BB,
 xxx= 265 to 290 in step of 5;
 JAM6(K)(SE)-60-xxx/PR, JAM6(K)(BK)(SE)-60-xxx/PR,
 JAM6(K)(TG)-60-xxx/PR, JAM6(K)(BK)(TG)-60-xxx/PR,
 xxx= 275 to 300 in step of 5;
 JAM6(L)(SE)-72-xxx/PR, JAM6(L)(BK)(SE)-72-xxx/PR,
 JAM6(K)(SE)-72-xxx/PR, JAM6(K)(BK)(SE)-72-xxx/PR,
 JAM72S05-xxx/PR, JAM72S07-xxx/PR, xxx= 325 to 330 in step of 5;
 JAM6(K)(SE)-72-xxx/4BB, JAM72S05-xxx/SC, xxx= 320 to 330 in step of 5;
 JAM72S02-xxx/PR, xxx= 325 to 390 in step of 5;
 JAM60S02-xxx/PR, xxx= 280 to 325 in step of 5;
 JAM72S02-xxx/SC, xxx =320 to 365 in step of 5;
 JAM60S02-xxx/SC, JAM60S05-xxx/SC, JAM60S07-xxx/SC,
 xxx =265 to 300 in step of 5;
 JAM72S08-xxx/PR, xxx = 355 to 400 in step of 5;
 JAM60S08-xxx/PR, xxx = 295 to 335 in step of 5;
 JAM72S12-xxx/PR, xxx= 370 to 390 in step of 5;
 JAM72S13-xxx/PR, xxx= 370 to 390 in step of 5;
 JAM72S14-xxx/PR, xxx= 370 to 390 in step of 5;
 JAM72S15-xxx/PR, xxx= 370 to 390 in step of 5;
 JAM72S16-xxx/PR, xxx= 370 to 390 in step of 5;
 JAM60S12-xxx/PR, xxx= 310 to 325 in step of 5;
 JAM60S13-xxx/PR, xxx= 310 to 325 in step of 5;
 JAM60S14-xxx/PR, xxx= 310 to 325 in step of 5;
 JAM60S15-xxx/PR, xxx= 310 to 325 in step of 5;
 JAM60S16-xxx/PR, xxx= 310 to 325 in step of 5;
 JAM72S17-xxx/PR, xxx= 380 to 415 in step of 5;
 JAM60S17-xxx/PR, xxx= 315 to 345 in step of 5;
 xxx is standing for rated output power at STC



